

# Making headway!



## WAKOL D 3125 LVT Flooring Adhesive

- Long-lasting – open time up to 180 minutes
- Extremely economical – large areas with low consumption
- Clean – no adhesive emerging at the joint
- Easy to install – possible to install on the area

Product:



**WAKOL®**  
Anspruch verbindet



# WAKOL D 3125 LVT Flooring Adhesive – Easy installation without any restrictions!



## New generation of adhesive – Advantages of all systems combined

Install LVT flooring, PVC and CV flooring in sheets and tiles in a modern way.

WAKOL D 3125 LVT Flooring Adhesive combines the advantages of the previous systems.

- Safety and strength of a wet adhesive
- Long open time of pressure sensitive adhesives
- Low consumption of roller adhesive

## Safety and strength of a wet adhesive

Even 3 hours after application WAKOL D 3125 LVT Flooring Adhesive satisfies the requirements in accordance with DIN standard 14259. The adhesive far exceeds the requirements of peel and shear values. Like a wet adhesive, WAKOL D 3125 LVT Flooring Adhesive securely holds the flooring on the subfloors.

The very low-emission WAKOL D 3125 LVT Flooring Adhesive is classified according to EMICODE EC1 PLUS.

## Sustainable thanks to low consumption and high cost-effectiveness

In contrast to roller adhesives, priming is not required on the levelling compound. WAKOL D 3125 LVT Flooring Adhesive is applied directly with a TKB A1 trowel. The consumption is just 190-220 g/m<sup>2</sup> and therefore considerably below that of traditional wet adhesives. As a result, less material has to be transported to the construction site.

As a standard-conforming adhesive with building approval, it can be used for tendering and public areas.



## Long open time

After the airing time the flooring can be laid in the adhesive bed up to 3 hours. This makes it possible to apply WAKOL D 3125 LVT Flooring Adhesive to large areas. Even complicated patterns or room geometries can now be completed safely and reliably and without any time pressure.

## Fast and comfortable usage

WAKOL D 3125 LVT Flooring Adhesive is suitable for laying on absorbent and non-absorbent subfloors. The adhesive is very easy to spread with the TKB A1 trowel and therefore easy to apply. Based on these properties, WAKOL D 3125 LVT Flooring Adhesive can also be easily used when standing with corresponding tools.

Proven installation techniques reinterpreted – with WAKOL D 3125 LVT Flooring Adhesive it is possible to work on the new installed floor without adhesive emerging from the joints. The area is suitable for walking directly after the flooring is laid.

Please always observe the technical information before processing.