

# WAKOL NE 479 Contact Adhesive

## Technical Information

### Area of application

Neoprene adhesive for skirting boards and the stair installation of textile-, homogeneous PVC-, rubber-, natural cork-, and linoleum floorings on absorbent and non-absorbent subfloors.

### Special properties



- suitable for chairs with castors
- suitable over underfloor heating

1) Emissions class according to French law

### Technical data

Raw material base:	polychloroprene
Cleaning agent and thinner:	WAKOL RV 105 Neoprene Dilution
Method of application:	both sides with a smooth or fine-dented spatula, with a brush for skirting boards
Consumption:	approx. 200 - 300 g/m <sup>2</sup> , depending on the size of the spatula, the subfloor and the flooring
Waiting time:	approx. 15 minutes, depending on the size of the spatula, the subfloor and the flooring
Laying time:	approx. 50 minutes
Storage temperature:	store in a cool place but not below +5°C
Storage time:	12 months at room temperature
GISCODE:	S1

## Subfloors

The subfloor and the room climate conditions must satisfy the requirements of DIN 18356. Subfloors must be level, permanently dry, firm, free of cracks, contamination and substances which hinder bonding.

Uneven subfloors must be levelled with Wakol levelling compounds. Respect the technical information of the primers and levelling compounds.

Cast asphalt must always be levelled.

## Usage

Stir adhesive well before use. Apply evenly to the subfloor and the backside of the floor covering with a smooth or fine-dented spatula avoiding globs of glue. Lay floor covering to fit after the appropriate waiting time and rub down well. It is not possible to make corrections later.

The floor covering can be welded the next day.

Bonded areas should be protected from exposure to direct sunlight during handling and final setting (approx. 3 days).

## Important

Do not use below +15°C. In cold weather warm adhesive in the heated room in due time.

For bonding CV-floorings with contact method respect particularities. Please contact our technical department before starting with work.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at [www.wakol.com](http://www.wakol.com).

This Technical Information of 16.07.2012 supersedes all previous versions.