

WAKOL KB 185 Skirting Adhesive Tape, 50 mm

Technical Information

Area of application

Strong adhesive tape on both sides with scrims for bonding

- Looped carpet skirting board with different backing
- Soft skirting (up to 60 mm)
- Rubber skirting (up to 60 mm)

indoors.

Special properties



1)



2)

- High ageing resistance
- High plasticiser resistance
- For textured subfloors up to maximum grain size of 1,5 mm

1) Based on the criteria of GEV (Association for Emission-controlled Laying Materials), classified as EMICODE EC1 PLUS: very low in emissions

2) Emissions class according to French law

Technical data

Raw material base:	Acrylate primer, woven material, paper
Dimensions:	50 m long, 50 mm wide
Thickness:	0,23 mm
Storage temperature:	not sensitive to frost

Subfloors

The subfloor must satisfy the requirements of the applicable standards and data sheets. Subfloors must be solid, level, free from cracks, dirt and adhesion-inhibiting substances.

WAKOL KB 185 Skirting Adhesive Tape, 50 mm can be applied on firm, smooth plasters, corrugated texture plasters (texture max. 1.5 mm grain size), brickwork, metal (untreated),

paint that cannot be removed, fixed wallpaper (in case of doubt remove at height of adhesive tape), wooden subfloors, concrete, gypsum subfloors or levelling compound, as well as stripped tiles. Precoat dusty and lightly sanded subfloors with WAKOL D 3003 Dispersion Primer or WAKOL D 3004 Primer Concentrate, elongated with water at ratio of 1:2. Note drying times for the different subfloors.

Usage

Adequately acclimatise materials before the work . Attach adhesive tape with roller or by hand to the wall or skirting. Remove protective paper and press on skirting board – do not overstretch. Press firmly down with hand roller, seam hammer or rubber hammer (white).

Important

Processing not below floor temperature of +15 °C and room temperature of +18 °C, as well as room humidity preferably between 40 % and 65 %, maximum 75 %. All information is based on approx. 20 °C and 50 % relative air humidity.

For tension at the ends of skirting boards, also use steel pins or clamps.

Warm up all laying materials in due time in heated room.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the current national standards must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.

This Technical Information of 26.09.2023 supersedes all previous versions.