

Adhesive Recommendations for Resilient Flooring

Subfloors	Concrete Slab with sufficient smooth and level surface*1	Plywood or OSB	Newly leveled subfloors with Wakol leveling compounds	WAKOL RP 104 Decoupling Sheet WAKOL TS 102 Sound Dampening Underlayment WAKOL TS 145 Sound Dampening Underlayment WAKOL TS 142 Sound Dampening Underlayment WAKOL TS 140 Sound Dampening Underlayment
Flooring				
PVC flooring, homogeneous	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320 WAKOL D 3318 WAKOL D 3120	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320 WAKOL D 3318 WAKOL D 3120	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320 WAKOL D 3318 WAKOL D 3120	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320
PVC bond flooring with polyester fleece Backing and CV flooring	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320 WAKOL D 3318 WAKOL D 3120	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320 WAKOL D 3318 WAKOL D 3120	WAKOL MS 552 WAKOL MS 550 WAKOL D 3330 WAKOL D 3320 WAKOL D 3318 WAKOL D 3120	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320
LVT Flooring	WAKOL MS 552 WAKOL MS 550 WAKOL D 3330 WAKOL D 3320 WAKOL D 3318 WAKOL D 3120	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320 WAKOL D 3318 WAKOL D 3120	WAKOL MS 552 WAKOL MS 550 WAKOL D 3330 WAKOL D 3320 WAKOL D 3318 WAKOL D 3120	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320
Rubber flooring with smooth, grinded backing	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320 WAKOL D 3318	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320 WAKOL D 3318	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320 WAKOL D 3318	WAKOL MS 552 WAKOL MS 550 WAKOL D 3320
PVC flooring, conductive			WAKOL DL 3365	

*1 surface roughness may telegraph through the flooring

All subfloors must meet NWFA guidelines.

For all cases that are not presented in the table above, please consult Loba-Wakol LLC - Telephone: (800) 230-6456